



**County of San Bernardino • Department of Public Health  
Division of Environmental Health Services  
COMMUNITY ENVIRONMENTAL HEALTH PROGRAM  
RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

www.sbcounty.gov/dph/dehs

(800) 442-2283

FACILITY NAME <b>QUALITY INN</b>					DATE <b>7/9/2014</b>	SIGNATURE <i>[Signature]</i>	
LOCATION <b>1750 S WATERMAN AV, SAN BERNARDINO, CA 92408</b>					REINSPECTION DATE <b>Not Specified</b>	PERMIT EXPIRATION <b>1/31/2015</b>	
MAILING ADDRESS <b>1750 S WATERMAN AV, SAN BERNARDINO, CA 92408</b>					REHS <b>Amanda Gaspard</b>		
FA # <b>FA0006654</b>	PR # <b>PR0014803</b>	SR # <b>Not Specified</b>	CO # <b>Not Specified</b>	PE <b>3623</b>	PROGRAM IDENTIFIER: Spa SERVICE: 001 - INSPECTION - ROUTINE		
TIME IN <b>10:01 AM</b>	TIME OUT <b>11:12 AM</b>	CONTACT <b>Not Captured</b>			RESULT: 05 - CORRECTIVE ACTION / FOLLOW UP REQUIRED ACTION: 13 - PERMIT SUSPENDED / FACILITY CLOSED		

**RECREATIONAL HEALTH - Public Pool - Additional Spa at Facility**




Based on an inspection this day, the items marked below identify the violation(s) in operation or facilities which must be corrected. The Permittee has the right to a hearing if requested in writing within 15 calendar days of receipt of this notice, to show cause why the permit to operate should not be suspended or revoked.

Failure to correct listed violation(s) prior to the designated compliance date may necessitate an additional reinspection at a charge of \$61.25 per 15 minutes with a minimum time of 30 minutes, and a minimum charge of \$122.50.

**76**

SCORE

Ideal
In Compliance
Not in Compliance



temperature (F)	109.0
observed flow (gpm)	No Data
required flow (gpm)	No Data
volume (gal)	No Data
area (sq ft)	No Data
occupancy	6

**36K402 Water Quality - Critical - Lack of Disinfectant**

**⚠ CRITICAL ⚠**

<b>POINTS</b> <b>4</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed that the chlorine level was 0.2 in the spa.  Ensure that chlorine level is between 1.5 and 10.0 ppm (since cyanuric acid is being utilized as a stabilizer). If a stabilizer is not used, ensure that chlorine level is between 1.0 and 10.0 ppm.  The spa is now closed due to inadequate chlorine. Contact the County of San Bernardino, Division of Environmental Health Services (DEHS) when compliance is reached. Maintain spa closed until re-opened by DEHS inspector.
	Not In Compliance	
	Violation Reference - CCR - 65529	

**Violation Description:** For pools using hypochlorite or gaseous chlorine without a stabilizer, a free chlorine residual at least 1.0 ppm shall be maintained throughout the pool. If cyanuric acid or a chlorinated isocyanurate is used, a free chlorine residual of at least 1.5 ppm shall be maintained throughout the pool.

**36K420 Temperature - Critical - Spa Water Requirement**

**⚠ CRITICAL ⚠**

<b>POINTS</b> <b>4</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed water temperature of spa at 109F.  Ensure that the water temperature of spa does not exceed 104F.  The spa is now closed due to high water temperature. Contact the County of San Bernardino, Division of Environmental Health Services (DEHS) when compliance is reached. Maintain spa closed until re-opened by DEHS inspector.
	Not In Compliance	
	Violation Reference - CCR 24 - 3138B	

**Violation Description:** The allowable water temperature of a spa pool shall not exceed 104°F.

**36K418 Water Quality - Cyanurates**

<b>POINTS</b> <b>2</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed cyanuric acid concentration in excess of 100 ppm. This is a repeat violation.  Ensure that cyanuric acid concentration does not exceed 100 ppm.
	Not In Compliance	
	Violation Reference - CCR - 65529	

**Violation Description:** The cyanuric acid concentration in any pool shall not exceeded 100 ppm.

**36K426 Safety - Emergency Shut-Off Switch**

<b>POINTS</b> <b>2</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed that the emergency shut-off switch was broken / missing. This is a repeat violation.  Repair / replace emergency shut-off switch immediately. Ensure that a functional emergency shut-off switch is provided within 72 hours.  Inspector will conduct a re-inspection to determine compliance. Failure to comply by the deadline may result in additional billable re-re-inspections.
	Not In Compliance	
	Violation Reference - CCR - 3138B	

**Violation Description:** A clearly labeled emergency shut off switch for the control of both the recirculation system and the aeration and/or jet system shall be installed adjacent to the spa pool.



County of San Bernardino • Department of Public Health  
 Division of Environmental Health Services  
**COMMUNITY ENVIRONMENTAL HEALTH PROGRAM**  
**RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

[www.sbcounty.gov/dph/dehs](http://www.sbcounty.gov/dph/dehs)

**(800) 442-2283**

FACILITY NAME <b>QUALITY INN</b>	DATE <b>7/9/2014</b>	SIGNATURE 
LOCATION <b>1750 S WATERMAN AV, SAN BERNARDINO, CA 92408</b>		REHS <b>Amanda Gaspard</b>

**36K427 Safety - Safety Signs**

<b>POINTS</b> <b>2</b>	Compliance Date: <b>Not Specified</b>	<b>Inspector Comments:</b> Observed that the following signs are missing: 1) Sign with the name and street address of the facility 2) Sign with the number of the nearest local emergency services [note: this is in additional to the 911 sign].  This is a repeat violation.  Provide signs.
	Not In Compliance	
	Violation Reference - <b>CCR 24 - 3120B</b>	

**Violation Description:** All signs shall have clearly legible letters or numbers not less than 4 inches high, unless otherwise required, affixed to a wall, pole, gate or similar permanent structure in a location visible to all pool users. The following shall be posted:

- a) Maximum number of pool users permitted for each pool.
- b) "NO DIVING" at pools with a maximum water depth of 6 feet or less.
- c) Where no lifeguard service is provided, a warning sign shall be posted stating, "WARNING: NO LIFEGUARD ON DUTY." The sign also shall state in letters at least 1 inch high, "Children under the age of 14 shall not use pool without a parent or adult guardian in attendance."
- d) An illustrated diagram with text at least 1/4 inch high of artificial respiration and CPR procedures.
- e) The emergency telephone number 911 with numbers not less than 4 inches (102mm), the number of the nearest emergency services and the name and street address of the pool facility with numbers and text not less than 1 inch (25 mm) shall be posted.
- f) A warning sign for spa pools with "CAUTION" language.
- g) Where pools were constructed for which lighting was not required, a sign shall be posted at each pool entrance on the outside of the gate(s) stating, "NO USE OF POOL ALLOWED AFTER DARK."
- h) A sign shall be posted on the exterior side of gates and doors leading into the pool enclosure area stating, "KEEP GATE CLOSED" or "KEEP DOOR CLOSED".
- i) A sign in letters at least 1 inch high and in a language or diagram that is clearly stated shall be posted at the entrance area of a public pool which states that persons having currently active diarrhea or who have had active diarrhea within the previous 14 days shall not be allowed to enter the pool water.
- j) A sign in letters at least 1 inch high shall be posted that describes the requirements for wave pools.
- k) A sign shall be posted at each spray ground and be visible from any part of the spray ground that states, "CAUTION: WATER IS RECIRCULATED. DO NOT DRINK."

**36K440 Enclosure - Non-Critical - Enclosure/Gates Non-Drowning Hazard**

<b>POINTS</b> <b>2</b>	Compliance Date: <b>Not Specified</b>	<b>Inspector Comments:</b> Observed that fencing (near the gate to the spa) was rusted / corroded. The fencing was particularly rusted / corroded at the section adjacent to the latch area for the gate. [Note: the gate is properly self-latching / self-closing as required.]  Maintain all fencing in good repair.
	Not In Compliance	
	Violation Reference - <b>HSC - 3119B</b>	

**Violation Description:** The enclosure, doors and gates shall meet all requirements in the California Code of Regulations. Fencing/gates shall be maintained in good repair.

**36K444 Equipment - Recirculation Pump/Filter/Separation Tank**

<b>POINTS</b> <b>2</b>	Compliance Date: <b>Not Specified</b>	<b>Inspector Comments:</b> Observed no directional symbols on piping in the equipment area.  Ensure that the direction of flow for the recirculation equipment is clearly labeled with directional symbols such as arrows on all piping in the equipment area.
	Not In Compliance	
	Violation Reference - <b>HSC - 3120B, 3132B, 3141B</b>	

**Violation Description:** Each pool shall be provided with a separate recirculation system designed for the continuous recirculation, filtration and disinfection of the pool water. The pumps, filters and all related parts of the pool water purification system shall be kept in operation whenever the pool is available for use. All parts of the pool and related pool facilities and equipment shall be maintained in good repair.

The backwash from a diatomaceous earth filter shall discharge into a separation tank. The wastewater from the separation tank shall discharge into a sanitary sewer or other disposal system acceptable to the local wastewater agency.

The direction of flow for the recirculation equipment shall be labeled clearly with directional symbols such as arrows on all piping in the equipment area.

**36K448 Equipment - Flow Meter**

<b>POINTS</b> <b>2</b>	Compliance Date: <b>Not Specified</b>	<b>Inspector Comments:</b> Observed that there was no flow meter attached to the system. Observed that the pipe with the flow meter was entirely detached from the system, and laying on the ground in the pump room area.  Repair / replace flow meter; maintain flow meter functional and in good repair. Ensure that there is a flow meter attached to the system.
	Not In Compliance	
	Violation Reference - <b>CCR - 3125B</b>	

**Violation Description:** A flow meter shall be provided on each recirculation system accurate to within 10 percent of flow. Flowmeter shall be maintained in good repair, accurately displaying flowrate.



**COMMUNITY ENVIRONMENTAL HEALTH PROGRAM  
RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

[www.sbcounty.gov/dph/dehs](http://www.sbcounty.gov/dph/dehs)

(800) 442-2283

FACILITY NAME <b>QUALITY INN</b>	DATE <b>7/9/2014</b>	SIGNATURE 
LOCATION <b>1750 S WATERMAN AV, SAN BERNARDINO, CA 92408</b>		REHS <b>Amanda Gaspard</b>

**36K458 Maintenance - Test Kit/Daily Records**

<b>POINTS</b> <b>2</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed that daily logs were not being properly maintained. Observed records for only pH and chlorine, but not for cyanuric acid. Also observed that maintenance procedures, etc., were not recorded.  Ensure to properly maintain daily logs regarding operation, including readings of disinfectant residual, pH, cyanuric acid, and maintenance procedures such as cleaning of filters and quantity of chemicals used.
	Not In Compliance Violation Reference - CCR - 65523, 65529	

**Violation Description:** Appropriate test kits for measuring the pH, concentration of the disinfectant, and, when used, concentration of cyanuric acid shall be provided at each pool. The test kit shall be capable of testing for free chlorine residual.

The operator of each pool open for use shall keep a daily record of information regarding operation, including readings of disinfectant residual, pH and maintenance procedures such as cleaning of filters and quantity of chemicals used.

**36K472 Access - Steps - Handrails - Diving Area**

<b>POINTS</b> <b>2</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Observed loose hand railings at steps.  Ensure that hand railings at steps are not loose. Repair / replace.
	Not In Compliance Violation Reference - CCR - 3111B, 3113B	

**Violation Description:** Stairs shall be provided in the shallowest portion of a pool. Ladders shall be corrosion resistant and shall be equipped with slip resistant tread surfaces. Ladders shall be rigidly installed. Hand rails shall be provided at the top of both sides of each ladder and recessed steps and shall extend over the coping or edge of the deck. Diving boards and platforms shall be anchored to the pool deck, constructed of corrosion resistant material, designed and constructed to be easily cleanable and finished with a durable slip resistant material.

**Overall Inspection Comments**

Notes:  
1) Observed that in the daily logs, the pH and chlorine entries for today (07-09-14) had already been filled out for the afternoon's reading, for both the pool and spa. The inspection occurred in the morning, and therefore the afternoon had not occurred yet. The person-in-charge stated that the person who filled out the log must have been confused about the date. Ensure to properly record dates in the daily logs.

**Photo Attachments:**  
No Photo Attachments