



**Public Health**  
Environmental Health Services

**RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

FACILITY NAME <b>RADISSON ONTARIO AIRPORT</b>		DATE <b>5/5/2015</b>	REINSPECTION DATE <b>Not Specified</b>	PERMIT EXPIRATION <b>8/31/2014</b>
LOCATION <b>2200 E HOLT BL, ONTARIO, CA 91761</b>			INSPECTOR <b>John Ramos</b>	
MAILING ADDRESS <b>2155 E CONVENTION CENTER WY, ONTARIO CA 91764</b>			IDENTIFIER: Spa	
			SERVICE: 001 - INSPECTION - ROUTINE	
TIME IN <b>4:15 PM</b>	TIME OUT <b>5:00 PM</b>	FACILITY ID <b>FA0006518</b>	RELATED ID <b>PR0013910</b>	PE <b>3623</b>
			RESULT: 05 - CORRECTIVE ACTION / FOLLOW UP REQU	
			ACTION: 03 - REINSPECTION REQUIRED	

**RECREATIONAL HEALTH - Public Pool - Additional Spa at Facility**


Based on an inspection this day, the items marked below identify the violation(s) in operation or facilities which must be corrected. The Permittee has the right to a hearing if requested in writing within 15 calendar days of receipt of this notice, to show cause why the permit to operate should not be suspended or revoked.

**92**

SCORE

Failure to correct listed violation(s) prior to the designated compliance date may necessitate an additional reinspection at a charge of \$61.25 per 15 minutes with a minimum time of 30 minutes, and a minimum charge of \$122.50.

Ideal
In Compliance
Not in Compliance



temperature (°F)	No Data
observed flow (gpm)	No Data
required flow (gpm)	No Data
volume (gal)	No Data
area (sq ft)	No Data
occupancy	No Data

**36K524 Safety – Critical – Electrical hazards; GFCI** **⚠ CRITICAL ⚠**

<b>POINTS</b> <b>5</b>	Comply by: 5/7/2015	<b>Inspector Comments:</b> Observed GFCI has been bypassed. Reinstall the GFCI to the pool lighting system.
	Not in Compliance	
	Violation Reference - HSC - 116049	

**Violation Description:** The design and installation of all underwater lighting systems, operating at more than 15 volts, supplied from a branch circuit either directly or by way of a transformer, shall be installed in a public swimming pool so that there is no shock hazard with any likely combination of fault conditions during normal use, and shall comply with both of the following requirements:

- (1) An approved ground-fault circuit interrupter shall be installed in the branch circuit that supplies all fixtures operating at more than 15 volts.
- (2) Only approved underwater lighting fixtures shall be used and no lighting fixtures shall be installed for operations at more than 150 volts between conductors.

**36K527 Safety – Safety signs**

<b>POINTS</b> <b>1</b>	Comply by: 5/19/2015	<b>Inspector Comments:</b> Observed pool and spa capacity not listed on the safety signs. Provide capacity.
	Not in Compliance	
	Violation Reference - CCR - 3120B	

**Violation Description:** All signs shall have clearly legible letters or numbers not less than 4 inches high, unless otherwise required, affixed to a wall, pole, gate or similar permanent structure in a location visible to all pool users. The following shall be posted:

- a) Maximum number of pool users permitted for each pool.
- b) ""NO DIVING"" at pools with a maximum water depth of 6 feet or less.
- c) Where no lifeguard service is provided, a warning sign shall be posted stating, ""WARNING: NO LIFEGUARD ON DUTY."" The sign also shall state in letters at least 1 inch high, ""Children under the age of 14 shall not use pool without a parent or adult guardian in attendance.""
- d) An illustrated diagram with text at least 1/4 inch high of artificial respiration and CPR procedures.
- e) The emergency telephone number 911 with numbers not less than 4 inches (102mm), the number of the nearest emergency services and the name and street address of the pool facility with numbers and text not less than 1 inch (25 mm) shall be posted.
- f) A warning sign for spa pools with ""CAUTION"" language.
- g) Where pools were constructed for which lighting was not required, a sign shall be posted at each pool entrance on the outside of the gate(s) stating, ""NO USE OF POOL ALLOWED AFTER DARK.""
- h) A sign shall be posted on the exterior side of gates and doors leading into the pool enclosure area stating, ""KEEP GATE CLOSED"" or ""KEEP DOOR CLOSED"".
- i) A sign in letters at least 1 inch high and in a language or diagram that is clearly stated shall be posted at the entrance area of a public pool which states that persons having currently active diarrhea or who have had active diarrhea within the previous 14 days shall not be allowed to enter the pool water.
- j) A sign in letters at least 1 inch high shall be posted that describes the requirements for wave pools.
- k) A sign shall be posted at each spray ground and be visible from any part of the spray ground that states, ""CAUTION: WATER IS RECIRCULATED. DO NOT DRINK.""



## Public Health

### Environmental Health Services

[www.SBCounty.gov](http://www.SBCounty.gov)

### RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT

FACILITY NAME RADISSON ONTARIO AIRPORT	DATE 5/5/2015
LOCATION 2200 E HOLT BL, ONTARIO, CA 91761	INSPECTOR John Ramos

#### 36K528 Safety – Safety equipment

POINTS <b>1</b>	Comply by: 5/19/2015	<b>Inspector Comments:</b> Observed rescue pole not present in the pool area. Provide rescue pole. Corrected.
	Not In Compliance Violation Reference - HSC - 65540	

**Violation Description:** Except for spray grounds without standing water, the pool operator shall ensure that the following safety and first aid equipment is provided and maintained readily visible and available for use at the public pool at all times:

- (1) A 17-inch-minimum (exterior diameter) life ring with an attached throw rope with a minimum 3/16-inch diameter. The throw rope shall be of sufficient length to span the maximum width of the public pool and shall be stored in such a way as to prevent kinking or fouling.
- (2) A 12-foot-minimum fixed-length rescue pole with a permanently attached body hook. For spas, the length of the rescue pole shall be of sufficient length to effectuate rescue.

For public pools that exceed 75 feet in length or 50 feet in width, the pool operator shall provide a rescue pole and a life ring on at least two opposing sides of the public pool at centralized locations.

For public pools with lifeguard personnel on duty, the pool operator of each public pool area shall have the following additional safety equipment:

- (1) A Red Cross 10-Person Industrial First Aid Kit or the equivalent.
- (2) An operating telephone.
- (3) A backboard and head immobilizer.

#### 36K542 Enclosure – Non-Critical – Gates and doors self-closing and self-latching

POINTS <b>1</b>	Comply by: 5/7/2015	<b>Inspector Comments:</b> Observed 3 entry gates where the gates did not latch and close. Repair gates. Corrected by dead bolting the affected gates. Patrons can enter the pool area by other gates.
	Not In Compliance Violation Reference - CCR - 3119B	

**Violation Description:** Gates and doors shall be equipped with self-closing and self-latching devices. Gates and doors shall be capable of being locked during times when the pool is closed. The self-latching device shall keep the gate or door securely closed. Gates and doors shall open outwardly away from the pool except where otherwise prohibited by law. The pool enclosure shall have at least one means of egress without a key for emergency purposes. The enclosure shall be constructed so that all persons will be required to pass through common pool enclosure gates or doors in order to gain access to the pool area. All gates and doors exiting the pool area shall open into a public area or a walkway accessible by all patrons of the pool.

#### 36K952 Drained Pool or Spa Inspection

POINTS <b>NA</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Performed a drained spa inspection. Spa drained due to problems with the air jets.
	Not In Compliance Violation Reference - HSC	

**Description:** An inspection was conducted at this time on a drained pool or spa. Contact DEHS prior to filling with water and/or operating.

#### Overall Inspection Comments

Correct the above noted violations.

#### Signature(s) of Acknowledgement

NAME:  
TITLE:

Total # of Images: 0