



**Public Health**  
**Environmental Health Services**

**RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

FACILITY NAME HACIENDA MOBILEHOME PARK		DATE 8/21/2015	REINSPECTION DATE Not Specified	PERMIT EXPIRATION 6/30/2015
LOCATION 2100 SOAPMINE RD, BARSTOW, CA 92311			INSPECTOR Michelle Saltis	
MAILING ADDRESS 708 E ALMOND AV, ORANGE CA 92866			IDENTIFIER: Pool	
<input type="checkbox"/> FACILITY <input type="checkbox"/> OWNER <input checked="" type="checkbox"/> ACCOUNT			SERVICE: 001 - INSPECTION - ROUTINE	
TIME IN 12:51 PM	TIME OUT 1:35 PM	FACILITY ID FA0007170	RELATED ID PR0014164	PE 3620
			RESULT: 05 - CORRECTIVE ACTION / FOLLOW UP REQU	
			ACTION: 13 - PERMIT SUSPENDED / FACILITY CLOSED	

**RECREATIONAL HEALTH - Public Pool - Initial Pool at Facility**

Based on an inspection this day, the items marked below identify the violation(s) in operation or facilities which must be corrected. Failure to correct listed violation(s) prior to the designated compliance date may necessitate an additional reinspection at a charge of \$4.08 per 1 minute with a minimum time of 30 minutes, and a minimum charge of \$122.50.




**91**

SCORE

Administrative Order to Show Cause (OSC): The Permittee has the right to a hearing if requested in writing within 15 calendar days of receipt of this notice, to show cause why the permit to operate should not be suspended or revoked; otherwise the right to a hearing shall be deemed waived.

See the following pages for the code sections and general requirements that correspond to each violation listed below.

Ideal
In Compliance
Not in Compliance



temperature (°F)	No Data
observed flow (gpm)	No Data
required flow (gpm)	49
volume (gal)	24,500
area (sq ft)	600
occupancy	30

**IMPORTANT: Replacement of Suction Outlet Covers**

Suction Outlet covers (anti-entrapment covers over main drains and skimmer equalizer outlets) shall be replaced upon expiration. The expiration (in years) is stamped on the front of each cover, indicating the amount of time the cover is valid after installation. Each replacement cover shall:

1. Meet the latest ANSI/APSP-16 performance standard
2. Be rated for the maximum designed flow-rate of the pump

Retain all records which indicate the make/model number of the replacement cover and date of installation. Records shall be made available to your inspector upon request.

**36K995 Permit - Suspension**

**CRITICAL**

POINTS  
**NA**

Compliance Date: Not Specified  
 Not In Compliance  
 Violation Reference - HSC

**Inspector Comments:** Pool permit is suspended due to gate not self closing/latching. A reinspection will be conducted within 72 hours to follow up on compliance. Failure to comply may result in a charged reinspection. Contact Environmental Health at 800-442-2283 with any questions or concerns.

Pool closure sign posted and gate zipped tied shut.

**Violation Description:** Violation(s) observed pose an immediate threat to public health and safety. The health permit to operate is hereby suspended and the pool/spa ordered closed until the listed violation(s) have been corrected and verified by Environmental Health Services (EHS). The facility is to remain closed until permission from EHS is given. Contact your inspector at your local office to schedule a reinspection to reinstate the health permit. The facility is posted closed; do not move, hide, or remove the sign. Reopening of the pool/spa without the approval by EHS, may result in an hourly billable Professional Services fee.

**36K540 Enclosure – Critical – Gates and doors self-closing and self-latching**

**CRITICAL**

POINTS  
**5**

Compliance Date: Not Specified  
 Not In Compliance  
 Violation Reference - CCR - 3119B

**Inspector Comments:** Immediately repair gate to self close/latch.  
 Observed gate not self closing.

**Violation Description:** Gates and doors shall be equipped with self-closing and self-latching devices. Gates and doors shall be capable of being locked during times when the pool is closed. The self-latching device shall keep the gate or door securely closed. Gates and doors shall open outwardly away from the pool except where otherwise prohibited by law. The pool enclosure shall have at least one means of egress without a key for emergency purposes. The enclosure shall be constructed so that all persons will be required to pass through common pool enclosure gates or doors in order to gain access to the pool area. All gates and doors exiting the pool area shall open into a public area or a walkway accessible by all patrons of the pool.



## Public Health

### Environmental Health Services

[www.SBCounty.gov](http://www.SBCounty.gov)

### RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT

FACILITY NAME <b>HACIENDA MOBILEHOME PARK</b>	DATE <b>8/21/2015</b>
LOCATION <b>2100 SOAPMINE RD, BARSTOW, CA 92311</b>	INSPECTOR <b>Michelle Saltis</b>

#### IMPORTANT: Replacement of Suction Outlet Covers

Suction Outlet covers (anti-entrapment covers over main drains and skimmer equalizer outlets) shall be replaced upon expiration. The expiration (in years) is stamped on the front of each cover, indicating the amount of time the cover is valid after installation. Each replacement cover shall:

1. Meet the latest ANSI/APSP-16 performance standard
2. Be rated for the maximum designed flow-rate of the pump

Retain all records which indicate the make/model number of the replacement cover and date of installation. Records shall be made available to your inspector upon request.

#### 36K504 Water Quality – Non-Critical – Disinfectant level low

<b>POINTS</b> <b>1</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Maintain free chlorine in pool water between 1-10ppm without cyanuric acid or 2-10ppm with cyanuric acid.
	Not In Compliance	
	Violation Reference - HSC - 65529	Observed free chlorine in pool waster measuring at .66ppm with cyanuric acid.

**Violation Description:** The minimum concentration of disinfectant residual in public pools shall be 1.0 ppm free-chlorine without cyanuric acid or 2.0 ppm free-chlorine with cyanuric acid. The minimum concentration of disinfectant residual in public spas, wading pools, and spray grounds shall be 3.0 ppm free-chlorine. The maximum concentration of disinfectant residual shall be 10.0 ppm free-chlorine.

The minimum concentration of bromine residual in public pools shall be 2.0 ppm. The minimum concentration of bromine residual in public spas, wading pools, and spray grounds shall be 4.0 ppm.

#### 36K548 Equipment - General Requirements - System Description

<b>POINTS</b> <b>1</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Provide a float assembly and spring valve in the pool skimmer.
	Not In Compliance	
	Violation Reference - CCR 24 - 3123B.1	Did not observe float assembly and spring valve in pool skimmer.

**Violation Description:** Each pool shall be provided with a separate recirculation system designed for the continuous recirculation, filtration and disinfection of the pool water. The system shall consist of pumps, filters, chemical feeders, skimmers or perimeter overflow systems, valves, pipes, connections, fittings and appurtenances.

#### 36K560 Equipment – Waste water

<b>POINTS</b> <b>1</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Provide a minimum of one inch air gap to prevent backflow.
	Not In Compliance	
	Violation Reference - CCR - 3141B	Observed waste water directly connected to sewer pipe.

**Violation Description:** There shall be no direct connection between the pool, its recirculation system or overflow drain to any sanitary sewer, storm drain or drainage system.

Material cleaned from filters and backwash water from any recirculation system shall be disposed in a manner that is acceptable to the local wastewater agency and will not create a nuisance. Backwash water shall not be returned to a pool. Pipes carrying wastewater from pools including pool drainage and backwash from filters shall be installed as an indirect waste in accordance with the requirements of Chapter 8 of the California Plumbing Code.

The backwash from a diatomaceous earth filter shall discharge into a separation tank that has been installed to collect the waste diatomaceous earth mixture. The wastewater from the separation tank shall discharge into a sanitary sewer or other disposal system acceptable to the local wastewater agency.

#### 36K584 Maintenance - Operating procedures/Manufacturers' instructions

<b>POINTS</b> <b>1</b>	Compliance Date: Not Specified	<b>Inspector Comments:</b> Repair/replace flow meter. Observed flow meter stuck.
	Not In Compliance	
	Violation Reference - HSC - 65521	

**Violation Description:** The pool operator shall maintain pool operating procedures at the public pool site for use by the pool operator and for inspection by the enforcing agent.

The pool operator shall maintain manufacturers' instructions for the operation and maintenance for all mechanical and electrical equipment and water treatment systems at the public pool site for use by the pool operator and for inspection by the enforcing agent.

#### Overall Inspection Comments

Pool permit is suspended due to gate not self closing/latching. A reinspection will be conducted within 72 hours to follow up on compliance. Failure to comply may result in a charged reinspection. Contact Environmental Health at 800-442-2283 with any questions or concerns.

Manager not available pre and post inspection.



**Public Health**  
**Environmental Health Services**

**RECREATIONAL HEALTH - OFFICIAL INSPECTION REPORT**

FACILITY NAME HACIENDA MOBILEHOME PARK	DATE 8/21/2015
LOCATION 2100 SOAPMINE RD, BARSTOW, CA 92311	INSPECTOR Michelle Saltis

**Signature(s) of Acknowledgement**

*SWA*

NAME: signature not available

TITLE:

Total # of Images: 0